




SIGN MODELS




10mm




12mm








16mm



19mm



25mm

	10mm	12mm	16mm	19mm	25mm
Pixel Configuration	SMD 3-in-1 	True Pixel, 1R, 1G, 1B 	True Pixel, 1R, 1G, 1B 	True Pixel, 1R, 1G, 1B Red Mono: 1R Amber Mono: 1A 	True Pixel, 1R, 1G, 1B 
Module Dimensions (H x W)	12" x 12"	12" x 12"	12" x 12"	12" x 12"	12" x 12"
Matrix Configuration	30 x 30 pixels	24 x 24 pixels	18 x 18 pixels	16 x 16 pixels	12 x 12 pixels
Color Capability	XVS: 73.7 quintillion	XVS: 73.7 quintillion W-series: 1.15 quintillion	XVS: 73.7 quintillion W-series: 1.15 quintillion	XVS: 73.7 quintillion W-series: 1.15 quintillion Mono: 4,096 shades	XVS: 73.7 quintillion W-series: 1.15 quintillion
Viewing Angle	150° horizontal, +15°/-45° vertical	140° horizontal, 70° vertical	140° horizontal, 70° vertical	140° horizontal, 70° vertical	140° horizontal, 70° vertical
Video Frame Rate	XVS: 30-60 frames/second	XVS: 30-60 frames/second W-series: 20 frames/second	XVS: 30-60 frames/second W-series: 20 frames/second	XVS: 30-60 frames/second W-series: 20 frames/second	XVS: 30-60 frames/second W-series: 20 frames/second
Field-adjustable Brightness	Up to 7,000 NITS	Up to 10,000 NITS	Up to 10,000 NITS	Color: Up to 10,000 NITS Mono: Up to 5,000 NITS	Up to 10,000 NITS
120 or 240 volt Single Phase 60Hz	✓	✓	✓	✓	✓
Character Height	2.8" or larger	3.5" or larger	4" or larger	5" or larger	7" or larger
Minimum Viewing Distance	28'	36'	50'	60'	80'
Ignite Content Management	✓	✓	✓	✓	✓
Live Video Capability	Available	Available	Available	Available	Available
On-Demand Diagnostics	✓	✓	✓	✓	✓